

Scotch® LabelGard™ Film Tape 821



Technical Data

May, 2003

Product Description	Scotch® LabelGard™ Film Tape 821 is a lightly tinted pink film tape designed for protecting labels and packaging lists. The synthetic adhesive is designed for easy handling and dispensing with low static. It also offers abrasion and moisture protection. Writing on the backing with No. 2 pencils, ball point, and many marking pens makes this label covering tape acceptable by the U.S. Postal Service and U.P.S.
----------------------------	--

Construction	Backing	Adhesive	Colors
	Acetate	Acrylic	Transparent pink

Typical Physical Properties	Note: The following technical information and data should be considered representative or typical only, and should not be used for specification purposes.		
			ASTM Test Method
	Adhesion to Steel:	25 oz./in. width (27 N/100 mm width)	D-3330
	Longitudinal Tensile Strength:	12 lbs./in. width (210 N/100 mm width)	D-3759
	Elongation at Break:	15%	D-3759
	Tape Thickness - Backing:	1.6 mil (0.040 mm)	D-3652
	Total:	2.5 mil (0.063 mm)	D-3652

Features	• Matte finish. • Cuts easily and easy to dispense. • Low static. • Write on surface. • Low glare surface. • Long aging.	• Stable in cold temperatures and will protect labels in freezer. • Tape looks unique. • Labels can be edited, corrected or rerouted easily. • Bar code scanning protection allows a non-glare read. • Most labels are not likely to yellow, pucker or dry out during normal label life.
-----------------	--	--

Available Sizes	Standard Widths:	2 in., 3 in., 4 in., 5 in., 6 in.
	Available by Special Order:	Custom widths and lengths available on request, subject to minimum order requirements.
	Core Size (ID):	3 in.
	Lengths:	72 yds., bulk only

Scotch® LabelGard™ Film Tape

821

Application Techniques	A line of in-stock manual dispensers is available including the Scotch® Tape Dispensers M-727, M-707, M-797 and P56.
Storage Conditions	Storage of Scotch® LabelGard™ Film Tape 821 is recommended at 70°F (21°C) and 40-50% relative humidity.
For Additional Information	To request additional product information or to arrange for sales assistance, call toll free 1-800-362-3550 or visit www.3M.com/packaging . Address correspondence to: 3M Industrial Adhesives and Tapes Division, Building 21-1W-10, 900 Bush Avenue, St. Paul, MN 55144-1000. Our fax number is 651-778-4244. In Canada, phone: 1-800-364-3577. In Puerto Rico, phone: 1-787-750-3000. In Mexico, phone: 52-70-04-00.
Important Notice	3M MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's application. Please remember that many factors can affect the use and performance of a 3M product in a particular application. The materials to be bonded with the product, the surface preparation of those materials, the product selected for use, the conditions in which the product is used, and the time and environmental conditions in which the product is expected to perform are among the many factors that can affect the use and performance of a 3M product. Given the variety of factors that can affect the use and performance of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for the user's application.
Limitation of Remedies and Liability	If the 3M product is proved to be defective, THE EXCLUSIVE REMEDY, AT 3M'S OPTION, SHALL BE TO REFUND THE PURCHASE PRICE OF OR TO REPAIR OR REPLACE THE DEFECTIVE 3M PRODUCT. 3M shall not otherwise be liable for loss or damages, whether direct, indirect, special, incidental, or consequential, regardless of the legal theory asserted, including, but not limited to, contract, negligence, warranty, or strict liability.

ISO 9002

This Industrial Adhesives and Tapes Division product was manufactured under a 3M quality system registered to ISO 9002 standards.



Industrial Business
Industrial Adhesives and Tapes Division
3M Center, Building 21-1W-10, 900 Bush Avenue
St. Paul, MN 55144-1000



Recycled Paper
40% pre-consumer
10% post-consumer

Printed in U.S.A.
©3M 2003 70-0710-0255-7 (5/03)