

RG303

130# BOPP UTILITY FILAMENT TAPE

DESCRIPTION

A medium strength fiberglass reinforced polypropylene tape combined with an aggressive "solventless" pressure sensitive adhesive. Provides excellent adhesion to corrugated cartons and outstanding holding power.

PRODUCT APPLICATIONS

For packaging, palletizing and unitizing applications.



3647 Cortez Road West | Bradenton, FL 34210 | USA
Customer Service: 800.IPG.8273 | 800.474.8273
Tape Technical Service: 877.447.4832
www.itape.com | info@itape.com

While we believe them to be reliable, the statements and information herein are only for general guidance and are not warrants or guarantees for accuracy and completeness. The user must, by test or otherwise, determine suitability for this purpose. There is no warranty of fitness for a particular purpose. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, including consequential, exceeding purchase price is excluded. No one is authorized by us to make oral warranties. We reserve the right to make changes without notice or obligation in our products and publications.

EFFECTIVE: 01/11

INTERTAPE POLYMER GROUP TECHNICAL DATA SHEET

NOMINAL VALUES

The following data are nominal values based on PSTC, ASTM and other standard test. The data should not be considered as specifications.

Backing	1.1 Mil (28μ) Biaxially Oriented Polypropylene Film
Adhesive	Synthetic Rubber/Resin
Reinforcement	Fiberglass
Adhesion to Steel (oz/in of width) (at 90 degrees peel angle)	49 (13.4 N/25mm)
Tensile Strength (lbs/in of width)	130 (569 N/25mm)
Elongation (at break)	3%
Total Thickness (mils)	4.2 (0.107mm)
Quick Stick (oz/in of width)	
To Kraft	8 (2.2 N/25mm)
To Steel	30 (8.2 N/25mm)
Color	Clear

